

A METHOD AND SYSTEM PROVIDING A DIGITAL CINEMA DISTRIBUTION NETWORK HAVING BACKCHANNEL FEEDBACK

This application claims priority of U. S. provisional patent application No.:
5 60,262,608, filed on January 18, 2001.

BACKGROUND OF THE INVENTION

1. Field of the Invention

10 This invention relates to a digital distribution network system, and in particular to a method and a system for distributing digital video, audio, and data content.

2. Description of the Related Art

15 Digital cinema is changing the manner in which films can be captured, delivered and viewed. Digital cinema promises to transform the movie industry, as it will allow for the shooting, editing, and distribution of a film to be completed entirely electronically.

20 Currently, the distribution of digital content is hindered by several factors including, for example, costs of converting to digital cinema technology, the limited bandwidth of available transmission networks and the security of digitally transmitted content.

25 Notwithstanding these factors, the demand for digital cinema is increasing. This increasing demand for digital cinema can be attributed, in part, to the benefits of digital cinema, such as, cost savings in the production, processing, and distribution of content.

PCT Publication Number WO 99/66728 discloses a system and method for secure electronic delivery of motion pictures in digital format to many end users simultaneously. The system includes a studio-distributor management system, a headend system, a theater
30 system, and a creator/editors system. Another example can be found in PCT Publication

Number WO 00/34825. This publication is related more specifically to a control system for a multi-projection room cinema.

What is needed is a digital distribution system that provides an efficient and flexible means for taking advantage of the rapidly changing digital cinema technology.

SUMMARY OF THE INVENTION

The teachings herein provide a digital distribution network (DDN) for the distribution of digital cinema content, including digital video, audio, and data, to end locations, typically digital cinemas or theaters. It is also within the scope of the teachings herein that the DDN distribute digital cinema content to home theaters, residences, PDAs, cell phones, and similar devices. The DDN described herein is flexible as it can be configured to provide the distribution of pre-recorded content, live content, video games, video conferencing, interactive content, and combinations thereof, in a variety of configurations. The DDN provides an end-to-end distribution system and method for digital content. The DDN also has an ability to control event scheduling, transmission of scheduling software, bi-directional teleconferencing for screenings and audience monitoring. The DDN can be remotely controlled and configured. Moreover, the operational status or health of the DDN, and each theater, may be remotely monitored and alarmed via a back channel that transmits information to a central location.

The DDN in accordance with these teachings furthermore provides a networked feedback mechanism, which may be wired or wireless, for audience monitoring. The DDN also includes an interface with a global data communications network for enabling theater viewers to interactively receive information concerning a scene being displayed, and for commenting on the DDN distributed films using, for example, web forums, chats, and email.

Furthermore, the DDN provides a secure network using encryption methods (e.g., IPSEC, NIST AES, and presently preferred 3 DES encryption techniques).

The transmission and event scheduling software is accessible via an internal Extranet.

In one aspect this invention provides a digital content distribution and viewing system that includes a source of at least one of pre-recorded or live digital content; a transport mechanism for distributing the digital content to a plurality of theater locations where the digital content can be viewed by an audience and, at the plurality of theater locations, video cameras for generating live video of the audience for transport to one or more viewing locations.

In another aspect this invention provides a digital content distribution and viewing system that includes a source of at least one of pre-recorded or live digital content; a transport mechanism for distributing the digital content to a plurality of theater locations where the digital content can be viewed by an audience; at the plurality of theater locations, audience input devices for generating audience input signals; and a backchannel for transporting the audience input signals to one or more locations. The backchannel can be implemented using any public or private telecommunications connection, including the Internet.

In a further aspect this invention provides a digital content distribution and viewing system that includes a source of at least one of pre-recorded or live digital content; a transport mechanism for distributing the digital content to a plurality of theater locations in combination with at least one script, where the theater locations enable the digital content to be viewed by an audience with theater equipment; at the theater locations, a store and forward server for receiving the digital content and the at least one script, and for executing the script for controlling actions of the theater equipment during the viewing of the digital content; and a backchannel for transporting to a central site a log that is descriptive of at least some of the actions and equipment capabilities, and an associated time stamp of when the action was performed.

In a still further aspect of this invention a digital content distribution and viewing system includes a source of at least one of pre-recorded or live digital content; a transport mechanism for distributing the digital content to a plurality of theater locations in a compressed, encrypted format using a first encryption technique, where the theater locations enable the digital content to be viewed by an audience with theater equipment; at the theater locations, a store and forward server for receiving said digital content, the store and forward server having an output coupled to an input of a digital projection system and operating to decompress and decrypt the digital content, and for encrypting the digital content using a second encryption technique before transmitting the digital content to the input of the digital projection system.

In yet another aspect, this invention provides an embodiment wherein there is interposed, between the output of the store and forward server and the digital projection system or inside the projection head, an interface module operable for decompressing and decrypting the digital content, and for encrypting the digital content using a second encryption technique before transmitting the digital content to the input of the digital projection system. In this latter embodiment the second encryption technique may include "light" encryption techniques such as data scrambling, and the interface module may include an MPEG codec. Fractal compression, wavelet compression, Multi-Layer DCT, and Adaptive Block Size DCT may also be used. It is also within the scope of the present invention that the transmitted audio and/or video be distributed in an uncompressed format.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an overall block diagram of an embodiment of the DDN of the present invention;

FIG. 2 is a block diagram depicting a satellite network transmission aspect of the DDN;

FIG. 3 is a block diagram of one embodiment of a DDN originating site for receiving input from a terrestrial network and a DDN satellite uplink;

FIG. 4 is a block diagram of a second embodiment of a DDN originating site having a satellite downlink and a DDN satellite uplink;

FIG. 5 is a block diagram depicting a first embodiment of a satellite network transmission and video conformance aspect of the DDN for the distribution of live events to both theaters and the DDN originating site for re-transmission on the network;

FIG. 6 is a block diagram depicting a further embodiment of a satellite network transmission aspect of the DDN for the conformance and distribution of live events to the DDN originating site for re-transmission on the network;

FIG. 7 is a block diagram of theater equipment and signal flow of the DDN of FIG. 1;

FIG. 8 is a block diagram of a teleconferencing configuration of the DDN of FIG. 1;

FIG. 9 is a block diagram illustrating an embodiment of the theater equipment configuration, including teleconferencing capabilities for the DDN;

FIG. 10 is an overall block diagram of the system architecture for the DDN of FIG. 1;

FIG. 11 depicts an exemplary film event script;

FIG. 12 depicts an exemplary live event script;

FIG. 13 is a block diagram of a further embodiment of this invention, wherein an interface unit is disposed between the store and forward server and the digital projection head; and

FIG. 14 is a high level block diagram showing a content data stream output from the store and forward server to the interface unit of FIG. 13, where the content includes embedded metadata for configuring the interface unit.

5

DETAILED DESCRIPTION OF THE INVENTION

As employed herein an “action” refers to any command acted upon by theater equipment. For example, closing the auditorium curtains or displaying a still image for 30 seconds are both examples of an action. Certain actions are recorded in a log with an associated time stamp and provided through a backchannel to a central control site so as to enable, for example, the tracking of the unauthorized use of film content and/or the tracking of advertisements played for viewers. The word “content” refers to a smallest displayable entity, for example, a single still frame, piece of video, or a single file. An “event” is one of a plurality of defined uses for a DDN (Digital Distribution Network) 1, such as viewing pre-recorded video, viewing live events, or video teleconferencing. A “program” is a group of actions that form a portion of an event or all of an event. A “script” is a mechanism by which a program performs actions. A “theater server” or “video server”, also referred to herein as a “store and forward server” and a “store/forward server” is a hardware/software device that stores, schedules and makes content available for play. Decoder as used herein should be understood to include at least the functions of decoding video images and decoding signals from the network (satellite or otherwise) that are to be sent to the video decoder.

10052915-011302

20

25

30

With general reference to the accompanying figures, and in particular to FIGS. 1, 7, 9 and 10, the overall system architecture of the DDN system 1 is described. DDN system 1 is referred to hereafter simply as the DDN 1. DDN 1 provides for the distribution of digital content, including video, audio, and data, to a plurality of theaters 2 from a content origination center 3 as well as from other sources. Other sources of content include, for example, a live feed source 6. The content can be any combination of video, audio, and data distributed as, for example, pre-recorded 5 or live content 6. A feature of the present invention is a capability for DDN 1 to provide bi-directional video teleconferencing between

theater 2 using a live audio/video system 7 located at theater 2. The bi-directional teleconferencing content is routed to a broadcast booth 50 via a live video/audio compression system 85, a caching server 80, a data router 45 and a network interface 40. Network interface 40 can interface with a wireless (e.g., satellite) and/or a terrestrial network.

5

A backchannel 4 is provided and may be established, for example, via a return transponder link through a satellite and/or a wired or wireless terrestrial data communications network, such as a terrestrial communications network or the Internet. A combination of different paths and transport mechanisms may be employed in tandem to implement backchannel 4.

Content server 10 can accommodate live content 6 and pre-recorded content 5. A further input to the uplink site 25 can be optional third party content that is sent directly to the uplink site 25. Content server 10 may receive live 6 and/or pre-recorded 5 content data from a variety of content origination source locations. Content server 10 may be implemented as a component of a content transport system 65 that may include a satellite transponder 30 associated with an uplink site 25 and a plurality of downlink sites 35. Each of downlink sites 35 is preferably associated with a theater 2 (see FIGS. 2 –6). Content server 10 is coupled to uplink site 25 via an appropriate intra-network 20. Downlink site 35 located at the theater 2 may include a satellite dish located on a roof of theater 2. A terrestrial network router 45 enables the content to be delivered via a terrestrial data network to those theaters 2 that do not support a satellite receiver downlink site 35.

At theater 2, a network interface unit 40 receives the transmitted content via transport mechanism 65, demodulates the transmission, and provides a digital output to router 45. Router 45 is connected to a caching server 80 on a LAN that may include a type of mass storage system for storing transmitted content received from content server 10, broadcast booth 50, and/or the third party providing third party content 21. A caching server 80 is coupled to store and forward server 75 (hereinafter store/forward server 75) or provides the functionality of a store/forward server. Store and forward server 75 provides an output of the

transmitted content to an audio playback system 110 via, for example, an AES link. Store and forward server 75 provides another output to a decryption and digital projection system 105 via an AV matrix 84. AV matrix 84 includes a digital projection system and may be any one of several commercially available digital projection systems. AV matrix 84 facilitates coupling multiple data content transmissions to projection system 105. Examples of suitable projection systems currently available include Texas Instruments Digital Light Processing™ (DPL) projectors, and Hughes-JVC's Direct-Drive Image Light Amplifier™ (D-ILA) projectors.

Caching server 80 (e.g., a PC) provides control, reporting, error logging, buffering and additional storage, if required. Caching server 80 directly, or store/forward server 75, provides a control output to a theater automation system 100. Theater automation system 100 is used for controlling theater lighting, a theater curtain (if present) and other automated theater controls, such as masking for different aspect ratios and lens changes. All of the functions controlled by theater automation system 100 are preferably coordinated by downloaded script files executed by store/forward server 75.

An aspect of these teachings is the ability to provide video and audio signals generated at theater 2 using one or more live video feeds 95 and microphones 90. The outputs of live video feeds 95 and microphones 90 are provided to a live video/audio compression system 85 that provides compressed video/audio signals to caching server 80. Caching server 80 in turn relays the compressed video/audio signals to terrestrial network router 45. From router 45 the live video/audio content can be transmitted to broadcast boot or telecommunications bridge 50. In this manner, and by example, a group meeting at theater 2 can conduct bi-directional, live video conferencing with one or more other persons located at, for example, a content origination location.

The live video feed(s) 95 and microphone(s) 90 can also be used to monitor the reactions of a test audience or focus group that is viewing an event, such as a film or an advertisement. The focus group can be monitored in real time at, for example, a content

origination location such as a film studio or any other point, or the live video/audio signals can be stored at the live video/audio compression system 85 (or another location) for subsequent playback. Timing signals received from the store/forward server can also be recorded by live video/audio compression system 85 for correlating the captured audience reactions to the content that invoked the recorded reactions.

In one aspect of the present invention, one or more of the live video feeds 95 may employ IR or low light cameras for viewing the audience under low-light theater conditions during the projection of the content. In addition, the audience may provide feedback on the content, be provided additional information regarding the content, or interact with the content via wired devices at each seat or wireless feedback devices, such as cell phones or PDAs.

In a preferred embodiment, the content leaving content server 10 is strongly encrypted to discourage unauthorized interception and viewing or recording of the transmitted signal. A function of the store/forward server 75 is to remove the strong encryption prior to playout, and to preferably provide in its place encryption on the link between store/forward server 75 and the decryption and projection unit 105, thereby discouraging unauthorized recording of the content in theater 2. In other embodiments, decryption/projection system 105 may be implemented and configured for removing the strong encryption, thereby eliminating this function from store/forward server 75.

It will be appreciated by those skilled in the art that various types of digital content can be distributed using the present invention, and that DDN 1 may be arranged in a variety of configurations. That is, the embodiment depicted herein are not intended to be viewed in a limiting sense upon the scope and practice of these teachings. Although DDN 1 is discussed herein primarily in the context of distributing digital content, either pre-recorded or live, to theaters 2 for viewing, and providing a video teleconferencing functionality, this is done in order to illustrate, and not limit, the teachings of this invention.

Viewing pre-recorded content

Referring to FIG. 1, content server 10 receives pre-recorded digital content 5 from a content source, such as from a content server controlled by the owner/provider of DDN 1. Caching server 80 located in theater 2 is polled or scheduled for communicating with content server 10 for providing content to caching server 80. Content server 10 may operate to “push” content to the theater-located store/forward servers 75. Content is requested or “pulled” in other embodiments. Content can also be sent to theater 2 and ingested into the caching server or store/forward server 75 using high density media. At theater 2, the store/forward server 75 receives content, stores it for archival purposes and forwards the content to other components of the theater-located system, including decryption and projection system 105 and audio playback system 110.

Store and forward server 75 located in a theater may be uniquely designated, either automatically or by a system administrator, to wait until content is flagged for reception. Backchannel 4, in some instances very small (e.g., a 56kbps dedicated dialup), is preferably provided so that various aspects of theater 2, including store/forward server 75, can be monitored, controlled, and updated with new scheduling scripts.

According to transmission scheduling software that is itself distributed to theaters 2, content is pushed to store/forward server 75 of the DDN 1. The time for displaying a film can be coordinated by, for example, a local marketing manager using an internal Extranet, or by any other suitable means.

At the beginning of an event, such as a film showing, theater automation system 100 identifies, via backchannel 4, the physical parameters of theater 2 and parameters of the equipment used for playback via a hardware abstraction layer present in all of the equipment. The execution of an event is described and specified by a collection of nested scripts, encapsulated into an overall event script that controls the event execution. The event script may be nested into a script that is executed by store/forward server 75 for controlling theater 2 for a given period of time, such as a day or a week. The event script is typically associated

with real time so that the scheduled events can be executed at the proper time and in the proper sequence. All other scripts can be time-independent.

Any of a number of suitable scripting languages may be employed. Examples of film and live event script are shown in FIGS. 11 and 12, respectively. The scripts are preferably distributed to store/forward server 75 as metadata along with the content that is to be viewed in theater 2.

In a presently preferred, but not limiting embodiment, an event begins with an advertising program containing still frames, video footage, and audio. The use of curtains, lights, and other cinema controls depends on a particular theater's facility. The script specifying the order and duration of the advertisements is sent to caching server 80 and forwarded to store/forward server 75 for execution. Store and forward server 75 may default to, by example, 29.97fps, or to the local television standard frame rate. All event duration calculations will be based on the operational frame rate. Store and forward server 75 preferably operates to mix at least two stereo audio streams. As the advertising program commences, a background audio stream is played using audio system 110. Audio files can also be linked to advertising content or, in the case of video content, embedded in the video file. The duration of the audio file event is set to match what is specified in the program script. Error checking may be provided on the script when it is generated and before it is loaded to store/forward server 75.

Content with attached audio may play over background music or preempt background music entirely. All audio transitions may be performed using a level fade. Store and forward server 75 preferably supports common audio formats. Video material (i.e., non-still frames) shown during the advertising program is recorded or scaled to the default rate before entering store/forward server 75. In addition, all material is preferably scaled to the standard resolution of digital projector 105 prior to entering store/forward server 75. The advertisements are preferably scaled to display properly with anamorphic and non-anamorphic films, depending on the main event content's needs. In the preferred

embodiment, DDN 1 uses the current native resolution of a Digital Light Processing (DLP) chip that forms a part of digital projection system 105.

In operation, the advertising program can be scripted to loop or to continuously fill the time between the end of an event (e.g., feature film) and the beginning of another event (e.g., the display of a movie trailer). The theater house lights are preferably dimmed to an appropriate level by theater automation system 100, and the trailer program starts. The trailer sequence is preferably treated like the advertising program discussed above. Trailers are encoded as described above so that there is no frame rate difference between advertising and trailer programs. Once the trailer program then finishes, the theater lights are then dimmed to their final level and any necessary adjustments are performed by theater automation system 110 in preparation for the playback of the pre-recorded film content 5. Film content 5 starts, appending multiple files in real time (using cuts or timed fades) for display. When the film is finished the next program or event starts.

A standard program audio used by DDN 1 is 5.1 digital audio. The system format can work in combination with Digital Theater System (DTS) or other audio formats such as Dolby E and Sony's SDDS, including multiple channel, uncompressed audio formats.

Some predetermined amount of time is preferably allotted for allowing cleaning of theater 2. The allotted time can be used as a buffer in case there are timing errors during the playback of the previous event script sequence or other timing delay circumstances. Caching server 80 is coupled to store/forward server 75 logs all aberrations such as timing delays.

An example of a typical prerecorded film event script is shown in FIG. 11. Nested scripts, as explained above, are used to control the entire event execution process. DDN 1 also preferably has some manual system function incorporated therein so that the timing of events (e.g., film showings) can be modified. For example, a theater manager may manually control caching server 80 to delay the showing of a film (i.e., override or modify an event

script). Preferably, manual control inputs will be flagged, monitored, and analyzed for system status purposes.

Viewing a live event

5 In an aspect of the present invention, live events may be coordinated by a local marketing manager via an internal Extranet. The operational frame rate for the live event is preferably matched to the local television standard and switched at the beginning of the event. All content, including the live event and any advertising prior to it, is mixed into the stream broadcast style. An ATSC decoder 82 decodes and passes the live content stream through AV matrix 84 to projector system 105 that displays the digital content. For this scenario, DDN 1 is configured to stream high-bandwidth, high-definition video to each theater 2. Backchannel 4, e.g., approximately 56 kbps, is used to monitor network and equipment health located at theater 2. An exemplary, simplified e live event script is shown in FIG. 12.

Video teleconferencing

10 In another aspect hereof, and referring to FIG. 8, each theater 2 may be provided with live feed video camera system 95 for video teleconferencing. Teleconferences may be coordinated by local or regional marketing managers via an internal Extranet. An appropriate amount of bandwidth of DDN 1 is preferably made available for the transmission of the teleconference content. The frame rate is preferably matched to the local television standard and switched at the beginning of the event, and proceeds as a one-to-many and many-to-many video teleconferencing or broadcast application. Before the event begins a check is made to ensure that video cameras 95 at each theater 2 are functioning and the allotted bandwidth is appropriate for each one.

20 The teleconferencing event begins, for example, with either a one-to-many teleconference or a videotape being played. If a video is played, it is mixed, broadcast style, into the video stream. When the videotaped segment is over, a moderator can open the discussion up to each location. Ideally, an aggregate backchannel 4 of approximately 10Mbps

can be maintained from each content origination point. In this aspect, it is desirable to provide a viewing center and a control room 165, at least one remote viewing facility 170 and/or stream the content to the Internet.

5 Marketing Research Groups

Marketing research groups, including focus groups for gathering marketing data, may be assembled and coordinated by regional marketing managers via the internal Extranet. The entire bandwidth of DDN 1 may be made available, if necessary, for the transmission of the focus group. The frame rate is determined and set at the beginning of the event.

10 The marketing research group application has a unique set of features. For example, there are low-light-level video cameras 95, or IR cameras, mounted in the theater 2 in such a way as to cover the entire audience (for example, either one camera 95 with a fisheye lens or four cameras 95 positioned in each quadrant of the theater auditorium or multiple cameras with remote pan, tilt, and zoom functionality). There are also one or more of the microphones 90 that record audience reaction, but, preferably, filter out the program material. This information, which may be suitably compressed by the optional compression unit 85, can be recorded on media such as, standard definition Mini-DV tapes by a MiniDV VCR 85 (see FIG. 9) or other recording mechanisms and/or transmitted over backchannel 4, in association
15 with time codes output from the store/forward server 75 (or an ATSC decoder), in time code synch with a projected film.

20 The start of a marketing research group event is similar to that of a film. Store and forward server 75 has the option of showing trailers and other filler before the event begins. When the film starts, the output of each camera 95 may be multiplexed and sent back via the
25 backchannel 4 to an optional viewing area (165, 170) for interested parties, such as studio executives, directors, producers, etc. to view. Time code information is preferably also sent to the optional viewing area to synchronize viewing of audience reaction to the distributed content. When audience reaction is recorded, analysis of the gathered market research data
30 may be performed at a later date.

The foregoing description provides an overview of the presently preferred embodiment of DDN 1. Further details are now provided as to various specific and exemplary implementations of DDN 1.

5

A 45Mbps (DS3) connection to an uplink provider, that provides and maintains the uplink equipment 25, can be installed as part of the transport segment 65. The bandwidth of DDN 1 can be expanded by leasing or renting, on an as-needed basis, an additional satellite transponder.

A wide-area terrestrial data communications network may also be employed as part of the transport segment 65 to provide the content to various theaters 2. One benefit of using the terrestrial network is that the available bandwidth can be readily increased to any desired amount for providing streaming video and audio of very high quality.

Another alternative of the present invention includes using a physical distribution network. That is, all distributed data and content are transferred manually using a portable recording medium (e.g., a DVD) and human interaction.

In the preferred embodiment, all of the applications for the network system are preferably Web browser-based. Feedback is gathered from the Web, comprising part of transport segment 65, and through wireless devices (an extension of the Web). Web sites are preferably timed or synchronized to the flow of content so that theater goers can access, in theater 2, details about the scenes currently being displayed in theater 2 and pages are accessible via the Web for viewers to comment about the films. In addition, Web boards (commonly called forums), chats, and e-mail are preferably also made available.

Viewers in theater 2 can be linked to backchannel 4 that can include the Internet. Viewers can be provided with handheld wireless devices for generating Web queries. In a presently preferred embodiment DDN 1 supports wireless viewer feedback mechanisms such

as WAP enabled devices, iMode, wireless Ethernet, and Bluetooth. Viewers may be enabled to enter queries and the like using personal digital assistants (PDAs) and other portable wireless devices. Small displays can be used by viewers for viewing responses, Web pages and the like. Content server 10, or another server, can be used for interacting with the viewers in the various theaters 2. An optional kiosk may also be employed at or as a point of sale (POS) for enabling users to register comments and reviews concerning a film that they have viewed, and to couple these comments and reviews via the backchannel 4 to the content origination location, or to some other location(s). The output of the optional POS kiosk can be coupled to the Internet for the purpose of communicating viewer provided comments and reviews to a content origination (or other) location. Wired or wireless devices may also optionally be built in to theater seats to allow viewers to register feedback, comments and reviews.

It can be appreciated that DDN 1 described thus far supports the distribution of a variety of digital video resolutions, and furthermore provides an ability to implement bi-directional, interactive teleconferencing to and from each theater 2. An ability to stream feeds into each theater 2 is also provided, enabling live events to be simultaneously viewed in each theater 2. DDN 1 also provides an ability to store content, a capability to forward content to various locations, a capability to provide for program and auditorium management, including scheduling, monitoring and reporting of DDN 1 events and status. Screen management software can be used to allow regional managers to (1) program screens from a pool of available content, and (2) provide teaser trailers and advertisements on theater screens or on plasma screens, in theater lobbies. Advertising management software can be employed to manage advertisement placement on screens. An ability to pull content directly from the store/forward servers is also provided, as is an ability to support a fade or a cut between programs that provides a mechanism to adjust credits or certain scenes for particular markets. A capability is also provided to support text overlays or character generators such that alternate subtitles can be chosen by the theater management software or metadata included with the content. DDN 1 is capable of managing video from 25Mbps (and lower) through at least 15Gbps, and furthermore has an ability to synchronize program material to time code or

genlock it to any other node on the network. An ability is provided to support alternate soundtracks that can be selected by the theater management software or metadata included with the distributed content. Also provided is an ability to support most common audio formats (e.g., mono, stereo, Dolby stereo, 5.1, 7.1, 10.2, etc.).

5

In another aspect hereof, when the final cut of a film is made it is then ready for digitization, compression, encryption, and transmission. The (post-filming) digitization step is not necessary for digitally recorded films. Video encoding and decoding for the store and forward content may be handled by the video servers, such as content server 10, and store and forward (video) server 75. Live content can optionally be compressed prior to transmission using, for example, MPEG compression technology or any other suitably applicable compression technology.

The digital audio system may also use encrypted audio, and the bandwidth thereof may be limited to 1Mbps or less. It will be appreciated by those skilled in the art that the transmitted audio signal could be uncompressed and the bandwidth used thereby could be, for example, 1.8Mbps for 12 channels of uncompressed audio.

In a preferred embodiment, content within DDN 1 that is used for exhibition is encrypted. Decryption may be handled by store/forward server 75 and/or by digital projector 105, if the projector is so enabled. In another embodiment described below in reference to FIGS. 13 and 14, the decryption is accomplished by an intermediate interface unit 76 that is disposed between store/forward server 75 and digital projection system 105. Preferably any decryption scheme that is selected for use may be up-graded as desired either by firmware or hardware. If programming is distributed on DVD-ROM, each DVD is preferably encrypted and password protected, and is also serialized. Also, watermarks may be used on a per screen basis, so that any bootleg (i.e., unauthorized) copy of a program or film content can be identified by place and time.

In the preferred embodiment of DDN 1, occurrences of digital content transfers to each theater 2 are logged. Each program that is played is also logged in theater 2 and subsequently reported using backchannel 4. Storage needs are constantly assessed using reports from the Extranet system to manage and maintain sufficient storage capacity on the caching server 80, as well as on store/forward server 75. Caching server 80 preferably employs a RAID 0+1 scheme of mass storage, though additional or alternative mass storage formats are within the scope of the invention. Bandwidth usage is also preferably monitored and reported, which can be an important consideration for live event planning, as well as for scheduling the delivery of content to the theaters. The health of DDN 1 (including network latency and integrity) is monitored in real time using, as one suitable example, a Novell™ Managewise software package. Alarms are set if a server does not respond to command and control input from the DDN 1 broadcast booth 50. It is desirable that each component of DDN 1 be SNMP compatible. Additional device monitoring and control can be performed by the scheduling and monitoring software included as part of DDN 1.

In the preferred embodiment all interactions within the DDN 1 are handled through an internal Extranet. The Extranet is a browser-based application that may manage the following exemplary tasks: (1) scheduling of content downloads for each theater 2, as well as live events over the satellite 30 or terrestrial network; (2) taking orders from theater representatives and scheduling for duplication of films; (3) command and control software that enables real-time monitoring and reporting on the satellite 30 network and/or on the terrestrial network; (4) command dial-up access for those theaters 2 with caching server 80 that are not connected to a network enabling them to report their status on a preferably schedule; (5) report software for marketing and businesses; (6) individually addressable screens that allow screen management software to place appropriate programming on each screen in theaters, as well as in the theater lobbies; and (7) screen management software that takes into account the available bandwidth with regard to all download requests and network requirements, including scheduled live events, to schedule available time to download programs.

Control and scheduling software that runs on the internal Extranet may perform the exemplary tasks and functions of providing (1) an ability to regulate and restrict the allowed viewing only to theater and times authorized by a global administrator; (2) an ability to rotate encryption keys based on the chosen encryption technology; (3) an ability to modify the transmission schedule; (4) an ability to monitor the operational status and health of the DDN 1; (5) an ability to log and confirm actions or group of actions by the theater equipment; and (6) an ability to allow each theater region to log ticket sales and attendance information.

The digital cinema equipment in theater 2 may support, inter alia, the exemplary functions of (1) the management of theater equipment, such as lighting and curtains; (2) the program status for each screen and any lobby monitors; (3) the assessment of ticket sales and actual attendance for each event; and (4) the scheduling and schedule reporting for film showings and other relevant events to Internet movie web sites comprising transport segment 65. Additionally, theater store/forward server 75 provides important operational control functions of the distribution network for each theater 2. Each store/forward server 75 preferably contains sufficient storage capacity and has sufficient bandwidth to support multiple (e.g., 4 digital projectors) digital projectors 105 and associated screens in each theater 2 (e.g., 45Mbps x 4 projectors = 180Mbps plus up to 10Mbps per (optional) preview screen in the theater lobby), as well as hot swappable RAID 0+1 disk arrays capable of holding four films (e.g., 40G per film x 4 films = 160G) plus any promotional material (e.g., video advertisements and trailers and (optional) lobby kiosk material). One device suitable for implementing store/forward server 75 is a QuBit™ server available from QuVIS, Inc. Additionally, there are suitable servers available from other manufacturers such as Grass Valley, Avica, EVS, and Technicolor Digital Cinema.

Projector system 105 preferably handled 24 hertz, as well as other possible frame rates. Examples of suitable projectors 105 that are currently available include, but are not limited to, Texas Instruments Digital Light Processing™ (DPL) projectors, and Hughes-JVC's Direct-Drive Image Light Amplifier™ (D-ILA) projectors.

In another aspect of the present teachings, a form generation capability is provided by DDN 1 as shown in FIG. 10. Forms, questionnaires, coupons, vouchers, or other information can be transmitted from a remote location form generator 150 to a data collection device 160 at theater 2 via transport mechanism 65 and data routing device 155. In another embodiment, the forms, questionnaires, coupons, vouchers, or other information can be locally transmitted from screen management system 102 to data collection device 160. Data collection device 160 can be a PDA, mobile telephone, portable computer, pager, or other device configured to receive the communication of the forms, etc. Data related to the transmitted the forms and provided in response thereto is transmitted back to form generator 150 via transport mechanism 65 utilizing the communication links employed therein.

Referring to FIG. 2, pre-recorded content is content that has been entirely gathered before an exhibition. To enable the broadcast of content at high speed (currently, approximately 40Mbps), DDN 1 is preferably configured to use windows of off-peak satellite time. Compressed files are sent from the central content server 10 to each theater server 75 at an off-peak time. Each theater 2 with satellite equipment preferably has a permanent connection to the Internet via a dedicated Public Owned Telephone System (POTS) dial-up line or other suitable connection such as DSL, Cable, or T1 connection. This enables DDN 1 to ensure that data packets are arriving at each theater 2. It also enables the reports on health and up-load status to occur on a periodic basis. Some theaters 2 may not be located in an area that is practical for satellite installation, such as in certain urban areas or where zoning laws prevent the use of satellite antennas. In these situations, a high speed land line connection such as, for example, a terrestrial DS3 connection can be employed. Content broadcasts are coordinated on both the terrestrial and satellite networks. In the event that a theater 2 has a DS3 connection, there is no need for the POTS line as the system health and status reports may be uploaded via the DS3 network.

Referring to FIG.3, if live content is not available via a satellite as part of transport segment 65, a commercial free, third party distribution feed 21 can be routed to the uplink center via a terrestrial network including terrestrial network router 120. Any necessary

conversion to a format native to projector system 105 can be performed by, for example, ATSC encoder 130. The feed is then routed over DDN 1 via satellite 30 and via the terrestrial network through terrestrial network router 125 for those theaters 2 that do not support satellite downlink capability.

5

Referring to FIG.4, live content may be made available via the satellite network forming part of transport segment 65 shown in FIG. 1. In this situation, the uplink provider receives a commercial-free distribution feed 21 at one of their dishes 140 from a broadcaster's satellite 135 or a terrestrial network, performs any necessary video conversion, and uplinks the live feed content to the DDN 1 using, for example, the ATSC encoder 130. This content data stream is also fed to those theaters 2 that are only accessible via the terrestrial network (e.g., the DS3 network) through the terrestrial network router 125.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190

delivery of content to theatres not equipped to receive satellite transmissions using terrestrial router 125.

As previously stated the content leaving content server 5 is strongly encrypted to discourage unauthorized interception and viewing or recording of the transmitted signal, and the store/forward server 75 decrypts the content prior to the display thereof. It was also stated that the store/forward server 75 may provide a lighter encryption (e.g., data scrambling). It should be appreciated that other types of encryption can be used on the link between store/forward server 75 and projection system 105 without departing from the scope of the present invention.

As such, FIG. 13 is a block diagram of a further embodiment of this invention, wherein an interface unit 76 is disposed between store/forward server 75 and digital projection system 105. In this embodiment the distributed content is stored in the received encrypted form in store/forward server 75 and subsequently transmitted, still encrypted (and compressed) to interface unit 76. The data may be in MPEG2 format, and can be transmitted over a SCSI or a fiber channel.

Referring also to FIG. 14, which shows a high level block diagram that includes the digital content data stream output from store/forward server 75 to interface unit 76, it can be seen that the digital content stream includes embedded metadata for configuring the interface unit 76.

In the embodiment depicted in FIGS. 13 and 14 interface unit 76 operates to decompress and decrypt the received data stream, and to provide the decompressed and lightly encrypted or scrambled data stream to the projector 105. In this case, an interface module 106 is installed in digital projector system 105 for decrypting or descrambling the content data stream before projecting same on the screen for the viewers.

Interface module 76 may include a 14-bit video codec to implement video decompression and processing. The use of the 14-bit or greater codec is preferred over a conventional 8-bit MPEG or similar codec in order to reduce the amount of color error over that experienced with the conventional 8-bit MPEG codec (typically about 2% color error when compared with uncompressed NTSC or PAL color coding, error is greater when compared to film). In a presently preferred embodiment, the content is not compressed, and instead is transmitted from content server 10 to theater 2 and digital projector system 105 in an uncompressed format.

It should be appreciated that it is desirable, but not necessary, to integrate the functionality of store/forward server 75 and interface unit 76 so as to arrive at the configuration depicted in FIG. 1. It is also desirable, but not necessary, to integrate the functionality of caching server 80 with store/forward server 75; and high definition or alternate video decoder 82, AV matrix 84 and store/forward server 75.

While described above in the context of presently preferred embodiments, those skilled in the art should realize that various modifications to these teachings can be made, and that the modified system will still fall within the scope of these teachings. As an example, the backchannel 4 can be used to support interactive gaming by audience members at the plurality of theaters 2. Further by example, these teachings are not intended to be limited to any of the various data formats, data rates, specific numbers of components, or to any of the specific examples of suitable system components that were disclosed above.